



# RIZZOLI®

FIRE SINCE 1912

## DECLARATION OF PERFORMANCE

ACCORDING TO REGULATION (EU) 305/2011

### N. 111

1.	Unique identification code of the product-type	:	<b>RVE 80</b>
2.	Type, batch or serial number (Art. 11-4)	:	<b>PRO 110 - PRO 130</b>
3.	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification	:	<b>Cooker burning and domestic heating solid fuel</b>
4.	Name or registered trademark of the manufacturer (Art. 11-5)	:	<b>Rizzoli S.r.l.</b>
5.	Name and address of the manufacturer	:	----
6.	System of assessment and verification of constancy of performance (Attachment 5)	:	<b>System 3</b> <b>ACTECO s.r.l. - (N.B. 1880)</b>
7.	Notified laboratory	:	<b>I-33084 Cordenons (PN)</b> <b>Via Amman, 41</b> <b>1880-CPR-032-15</b>
8.	<b>Declared performance</b>		
	Harmonized technical specification	:	<b>EN 12815:2001/A1:2004/AC:2007</b>
	<b>Essential characteristics</b>		
	Reaction to fire	:	<b>A1</b> <b>Minimum distances, in mm:</b>
	Distance to combustibile materials	:	<b>rear = 450, sides = 1, floor = 0, ceiling = 600, front = 1000</b>
	Risk of burning fuel falling out	:	<b>Pass</b>
	Emission of combustion products	:	<b>CO [0,051 %]</b>
	Surface temperature	:	<b>Pass</b>
	Electrical safety	:	<b>Pass</b>
	Cleanability	:	<b>Pass</b>
	Maximum water operating pressure	:	<b>-- bar</b>
	Flue gas temperature at nominal heat output	:	<b>T [150 °C]</b>
	Mechanical resistance	:	<b>NPD</b>
	Nominal heat output	:	<b>8,0 kW</b>
	Room heating output	:	<b>8,0 kW</b>
	Water heating output	:	<b>-- kW</b>
	Energy efficiency	:	<b>η [86,4 %]</b>
9.	The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.		
	<b>This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.</b>		

Trodene n.P.N., March 15<sup>th</sup> 2017

