



RIZZOLI®

FIRE SINCE 1912

DECLARATION OF PERFORMANCE

ACCORDING TO REGULATION (EU) 305/2011

N. 68

1.	Unique identification code of the product-type	: RA 50
2.	Type, batch or serial number (Art. 11-4)	: S 60
3.	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification	: Cooker burning and domestic heating solid fuel
4.	Name or registered trademark of the manufacturer (Art. 11-5)	: Rizzoli S.r.l.
5.	Name and address of the manufacturer	: ----
6.	System of assessment and verification of constancy of performance (Attachment 5)	: System 3 ACTECO s.r.l. - (N.B. 1880)
7.	Notified laboratory	: I-33084 Cordenons (PN) Via Amman, 41 Issued test report : 1880-CPR-031-14
8.	Declared performance	
	Harmonized technical specification	: EN 12815:2001/A1:2004/AC:2007
	Essential characteristics	Performance
	Reaction to fire	: A1
	Distance to combustibile materials	: Minimum distances, in mm: rear = 300, sides = 10, floor = 0, ceiling = 600, front = 800
	Risk of burning fuel falling out	: Pass
	Emission of combustion products	: CO [0,07 %]
	Surface temperature	: Pass
	Electrical safety	: Pass
	Cleanability	: Pass
	Maximum water operating pressure	: -- bar
	Flue gas temperature at nominal heat output	: T [200°C]
	Mechanical resistance	: NPD
	Nominal heat output	: 7,4 kW
	Room heating output	: 7,4 kW
	Water heating output	: -- kW
	Energy efficiency	: η [80,8 %]
9.	The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.	

Trodene n.P.N., November 03rd 2014

