



# RIZZOLI®

FIRE SINCE 1912

## DECLARATION OF PERFORMANCE

ACCORDING TO REGULATION (EU) 305/2011

### N. 67

1.	Unique identification code of the product-type	: ST 90 B
2.	Type, batch or serial number (Art. 11-4)	: ST 90 B
3.	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification	: <b>Cooker burning and domestic heating solid fuel</b>
4.	Name or registered trademark of the manufacturer (Art. 11-5)	: <b>Rizzoli S.r.l.</b>
5.	Name and address of the manufacturer	: ----
6.	System of assessment and verification of constancy of performance (Attachment 5)	: <b>System 3</b> <b>ACTECO s.r.l. - (N.B. 1880)</b>
7.	Notified laboratory	: <b>I-33084 Cordenons (PN)</b> <b>Via Amman, 41</b> Issued test report : <b>1880-CPR-021-15</b>
8.	<b>Declared performance</b>	
	Harmonized technical specification	: <b>EN 12815:2001/A1:2004/AC:2007</b>
	<b>Essential characteristics</b>	<b>Performance</b>
	Reaction to fire	: <b>A1</b> <b>Minimum distances, in mm:</b>
	Distance to combustibile materials	: <b>rear = 10, sides = 10, floor = 0, ceiling = 700, front = 800</b>
	Risk of burning fuel falling out	: <b>Pass</b>
	Emission of combustion products	: <b>CO [0,11 %]</b>
	Surface temperature	: <b>Pass</b>
	Electrical safety	: <b>Pass</b>
	Cleanability	: <b>Pass</b>
	Maximum water operating pressure	: <b>3 bar</b>
	Flue gas temperature at nominal heat output	: <b>T [201,9 °C]</b>
	Mechanical resistance	: <b>NPD</b>
	Nominal heat output	: <b>11,3 kW</b>
	Room heating output	: <b>4,7 kW</b>
	Water heating output	: <b>6,5 kW</b>
	Energy efficiency	: <b>η [80,3 %]</b>
9.	The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. <b>This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.</b>	

Trodene n.P.N., June 12<sup>th</sup> 2015

