



RIZZOLI®

FIRE SINCE 1912

DECLARATION OF PERFORMANCE

ACCORDING TO REGULATION (EU) 305/2011

N. 115

1.	Unique identification code of the product-type	:	X-PLUS
2.	Type, batch or serial number (Art. 11-4)	:	X-BASIC - X-PLUS - X-CHEF - X-VISION
3.	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification	:	Domestic heating solid fuel
4.	Name or registered trademark of the manufacturer (Art. 11-5)	:	Rizzoli S.r.l.
5.	Name and address of the manufacturer	:	----
6.	System of assessment and verification of constancy of performance (Attachment 5)	:	System 3 ACTECO s.r.l. - (N.B. 1880)
7.	Notified laboratory	:	I-33084 Cordenons (PN) Via Amman, 41 1880-CPR-006-18
8.	Issued test report	:	1880-CPR-006-18
	Declared performance		
	Harmonized technical specification	:	EN 13240:2001/A2:2004/AC:2007
	Essential characteristics		Performance
	Reaction to fire	:	A1
	Distance to combustible materials	:	Minimum distances, in mm: rear = 100, sides = 200, floor = 0, ceiling = --, front = 1200
	Risk of burning fuel falling out	:	Pass
	Emission of combustion products	:	CO [0,055 %]
	Surface temperature	:	Pass
	Electrical safety	:	Pass
	Cleanability	:	Pass
	Maximum water operating pressure	:	-- bar
	Flue gas temperature at nominal heat output	:	T [195 °C]
	Mechanical resistance	:	NPD
	Nominal heat output	:	7,7 kW
	Room heating output	:	7,7 kW
	Water heating output	:	-- kW
	Energy efficiency	:	η [87,1 %]
9.	The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.		
	This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.		

Trodene n.P.N., February 22nd 2018

